




10 GAUGE GALVANIZED STEEL WET-SET (REPLACEABLE) INSTALLATION INSTRUCTIONS



- Be sure that concrete is compliant with ADA guidelines and engineer's specifications to ensure that proper installation can be achieved.
- Slowly press tile into concrete starting at one side and continue
 placement until flush with the surface. (Fig. 1) IMPORTANT: Do not
 stand on tile during installation. For radius tile installation, see Radius
 Wedge-to-Tile Assembly installation sheet.
- Using a rubber mallet, tap the entire surface of the tile to ensure consolidation around the anchors. (Fig. 2)
 NOTE: Installing tiles after moisture is gone from the top will help control floating. If needed, weight may be added. (Fig. 3)
- 4. IMPORTANT: Using an edging tool, go around entire perimeter of the tile to allow for expansion. (Fig. 4)




- 5. Finish concrete to required specifications. **NOTE: Do not stand or walk on tile until concrete is fully cured.**
- Clean any excess concrete slurry that may have consolidated inside perimeter edge and on the top surface.





NOTE: If a tile is cut, new ¼" holes need to be drilled and anchors reinstalled along the edge.

Installation is now complete.

TufTile







1/8" Deep Troweled Edge

<u>Click here</u> for more information including an installation video tutorial.

Contact us at 888-960-8897 with questions.

